

Master Electrical Component List

Name	Location
S203	(CKT 8) IP harness, above the instrument cluster, approximately 4 cm (2 in) from the fog lamp switch, instrument cluster breakout
S204	(CKT 9) IP wiring harness, behind the IP near right side of the steering column, approximately 4 cm (2 in) from the data link connector breakout
S205	(CKT 17) IP wiring harness, below the IP near C201, approximately 14 cm (6 in) from the G201 breakout
S206	(CKT 541) IP wiring harness, right side of the steering column, approximately 4 cm (2 in) from the data link connector breakout
S207	(CKT 33) IP wiring harness, behind the left side of IP, approximately 36 cm (14 in) from the body control module
S208	(CKT 1340) IP Wiring Harness, left side of the IP Approximately 6 cm (2 in) from the Headlamp Switch breakout towards the driver information center.
S209	(CKT 39) IP wiring harness, behind the right side of the instrument cluster, approximately 20 cm (8 in) from the driver information center breakout
S210	(CKT 1450) Cigar Lighter Jumper Harness
S211	(CKT 1550) IP wiring harness, behind the center of the IP, approximately 11 cm (4 in) from the data link connector
S212	(CKT 308) IP wiring harness, behind the right side of the instrument cluster, approximately 13 cm (5 in) from the driver information center breakout
S213	(CKT 150) IP wiring harness, approximately 4 cm (2 in) from the blower motor resistors/control module breakout
S218	(CKT 1807) IP wiring harness, below right side of IP compartment, approximately 4 cm (2 in) from the blower motor resistor breakout
S219	(CKT 11) IP wiring harness, behind the top of the instrument panel cluster, approximately 9 cm (4 in) from the instrument panel cluster breakout
S220	(CKT 75) IP wiring harness, below the right side of the IP compartment, approximately 8 cm (3 in) from the C200 breakout
S221	(CKT 10) IP wiring harness, right side of the steering column, approximately 17 cm (7 in) from the data link connector breakout
S225	(CKT 835) IP wiring harness, right side of the steering column, approximately 5 cm (2 in) from the data link connector
S228	(CKT 3) IP wiring harness right side of IP approximately 1 cm (1 in) from the SDM breakout towards the fuse block - IP

S203 - S228