## **Master Electrical Component List**

Name	Location
S307	(CKT 1307) Body wiring harness, on the floor near center of the vehicle, approximately 20 cm (8 in) from the C325 in-line to the front floor console wiring harness
S308	(CKT 194) Body wiring harness, below the right side of the front passenger seat, approximately 11 cm (4 in) from the G302 breakout
S309	(CKT 49) Body wiring harness, below the right side of the front passenger seat, approximately 4 cm (2 in) from the G302 breakout
\$310	(CKT 143) Body Harness near right kick panel approximately 16 cm (6 in) from the C302 breakout
\$314	(CKT 294) Body wiring harness, below the right side of the front passenger seat, approximately 4 cm (2 in) from the G302 breakout
\$315	(CKT 295) Body wiring harness, below the right front passenger seat, approximately 10 cm (4 in) from the right wiring channel
S316	(CKT 351) Body wiring harness, below the right front passenger seat, approximately 17 cm (7 in) from the right wiring channel
\$330	(CKT 750) Driver seat wiring harness, below the driver seat, approximately 26 cm (10 in) from C311
S331	(CKT 340) Driver seat wiring harness, below the driver seat, approximately 36 cm (14 in) from C311
\$332	(CKT 2040) Driver seat wiring harness, below the driver seat, approximately 10 cm (4 in) from the lumbar adjuster relay breakout
\$374	(CKT 8) Front floor console wiring harness, near the automatic transaxle control, approximately 22 cm (9 in) from the automatic transaxle control position indicator bulb connector
\$375	(CKT 150) Front floor console wiring harness, near the automatic transaxle control, approximately 11 cm (4 in) from the automatic transaxle control connector
8376	(CKT 1020) Front floor console wiring harness, near the automatic transaxle control, approximately 4 cm (2 in) from the automatic transaxle control connector
S390	(CKT 350) Dome lamp wiring harness, near the center of the windshield header approximately 4 cm (2 in) from the windshield header courtesy/reading lamps breakout
\$393	(CKT 1393) Dome lamp wiring harness, approximately 4 cm (2 in) from the right courtesy lamp breakout