

Master Electrical Component List

Name	Location
S229	(CKT 26) IP wiring harness left side of IP approximately 6 cm (2 in) from the data link connector breakout towards the stoplamp switch
S230	(CKT 1450) IP wiring harness, on the right side of the steering column, approximately 4 cm (2 in) from the data link connector breakout
S236	(CKT 740) IP wiring harness, on the right side of the steering column, approximately 20 cm (8 in) from C200
S237	(CKT 800) IP wiring harness, behind the center of IP, approximately 30 cm (12 in) from the data link connector breakout
S238	(CKT 440) IP wiring harness, below the center of the IP, approximately 27 cm (11 in) from C240
S239	(CKT 351) IP wiring harness, on the left center of IP, approximately 4 cm (2 in) from the C200 breakout
S240	(CKT 239) IP wiring harness right side of IP approximately 17 cm (7 in) from the fuse block - IP
S249	(CKT 243) IP wiring harness, below the IP near C201, approximately 4 cm (2 in) from the G201 breakout
S257	(CKT 1393) IP wiring harness, behind the center of IP, approximately 24 cm (9 in) from the data link connector breakout
S259	(CKT 690) IP wiring harness, below the right side of the IP, near the blower motor, approximately 8 cm (3 in) from the blower motor resistors/control module breakout
S261	(CKT 12) IP wiring harness approximately 5 cm (2 in) from P100 behind the IP
S264	(CKT 1020) IP wiring harness, below the center of IP, approximately 34 cm (13 in) from C240
S266	(CKT 739) IP wiring harness, below the steering column near C201, approximately 21 cm (8 in) from the stoplamp switch
S273	(CKT 744) IP wiring harness, behind the right side of the instrument panel cluster, approximately 22 cm (9 in) from the remote control door lock receiver breakout
S285	(CKT 1550) IP wiring harness, on the right side of the steering column, approximately 14 cm (5 in) from the data link connector breakout
S289	(CKT 15) IP wiring harness, behind the right side of the instrument cluster, approximately 7 cm (3 in) from the driver information center breakout
S290	(CKT 14) IP wiring harness, behind the right side of the instrument cluster, approximately at the driver information center breakout
S303	(CKT 750) Body wiring harness, below the left side of the driver seat, approximately 5 cm (2 in) from the G301 breakout

S229 - S303